

COMPREHENSIVE CLUSTERWISE LINEAR REGRESSION FOR PAVEMENT MANAGEMENT SYSTEMS

Mukesh Khadka

Ph.D. Candidate

Cell: (702) 683-2722

Email: khadkam@unlv.nevada.edu

Alexander Paz, Ph.D., P.E., Corresponding Author

Associate Professor

Director, Transportation Research Center

Office: (702) 895-0571

Cell: (702) 688-3878

Fax: (702) 895-3936

Email: apaz@unlv.edu

<http://web.unlv.edu/centers/trc/paz/>

Civil and Environmental Engineering and Construction

University of Nevada, Las Vegas

4505 Maryland Parkway, PO Box 454007, Las Vegas, NV 89154-4007

ABSTRACT

A comprehensive mathematical program was formulated to determine simultaneously 1) an optimum number of pavement clusters, 2) cluster memberships of pavement samples, 3) cluster-specific significant explanatory variables, and 4) estimated regression coefficients for Pavement Performance Models (PPMs). Simulated Annealing coupled with All-Subset Regression was proposed to solve the mathematical programming. The proposed algorithm was capable to identify and address potential multicollinearity issues. All possible combinations of the explanatory variables were examined to select the best model that provided a balance among 1) the number of PPMs; 2) the number of explanatory variables; 3) the resources required to develop, maintain, and use these models; and 4) the explanatory power. For the dataset used in this research, 6-cluster models were determined as part of the optimum solution. The predictive capabilities of the resultant models were investigated, and results showed that the models provided few prediction errors without any overfitting issues.

INTRODUCTION

Pavement deteriorates over time due to the combined effects of traffic and environmental factors. To keep pavement in a serviceable condition, highway agencies primarily have two alternatives: 1) permit the pavement to deteriorate until its condition falls below the serviceability limit, and then perform rehabilitation or reconstruction work; or 2) intervene with the deterioration by performing a series of maintenance activities that retard the deterioration process and essentially delay the type of substantial failure requiring major rehabilitation or reconstruction.

Considering that a typical cost of the maintenance is 15% to 20% of the cost for rehabilitation or reconstruction (Hajj et al. 2010), agencies are more focused on preserving and maintaining existing facilities (Davies and Sorenson 2000; Labi and Sinha 2003). However, the challenge is to find the pavement segments that require maintenance as well as appropriate times to execute such activities. Hence, there is a need to develop a proactive approach to identify potential pavement segments for improvement. Pavement performance models (PPMs) – one of several critical components required to achieve this proactive approach – seek to capture historical patterns of pavement deterioration that can be used to estimate an appropriate time for maintenance so that the condition of a pavement can be improved before a serviceability limit is reached.

In practice, it is very important to achieve a balance among the number of PPMs; the number of explanatory variables; the resources required to develop, maintain, and use these models; and the associated explanatory power. To determine this balance, PPMs typically are developed by using clusters of pavement samples. Instead of estimating the cluster memberships by using statistical methods, a few predefined explanatory variables are used to assign pavement

59 samples into clusters. In terms of performance, clusters formed in this way likely include
60 heterogeneous pavement samples.

61 The existing state-of-the-art methods propose Clusterwise Linear Regression (CLR) to
62 determine pavement clusters and associated PPMs simultaneously, using a single objective
63 function. In CLR, various clusters are formed so that homogenous pavement samples, in terms of
64 the effects of the explanatory variables on the dependent variable of a present regression model,
65 are assigned within a cluster (Park et al. 2015). The homogeneity of pavement samples in a
66 cluster is defined by the effects of the observed values of explanatory variables on the estimated
67 dependent variable, the Present Serviceability Index (PSI), by the regression model.
68 Observations of all the pavement samples assigned to a cluster fit the same PPM such that the
69 overall sum of squared errors (SSE) within clusters is minimal.

70 CLR first was implemented by Spath (1979) for data partition and estimation of
71 regression models within each cluster, simultaneously. The approach has been expanded further,
72 and implemented in many studies (DeSarbo et al. 1989; Wedel and Steenkamp 1989; Lau et al.
73 1999; Carbonneau et al. 2011; Schlittgen 2011; Zhen et al. 2012; Tan et al. 2013; Lu et al. 2014).
74 However, in the field of pavement management, to the best knowledge of the authors, only four
75 studies (Luo and Chou 2006; Luo and Yin 2008; Zhang and Durango-Cohen 2014) have been
76 performed using CLR.

77 In a recent study (Zhang and Durango-Cohen 2014), CLR with multiple explanatory
78 variables was proposed to account for heterogeneity in pavement deterioration. The study used
79 the data collected during the AASHO Road Test (Highway Research Board 1962), which is no
80 longer the best available data nor representative of existing conditions. This data was collected at
81 a single site, and over 50 years ago, when materials and construction techniques were different.

The study estimated models with the objective of minimization of the residual sum of squares (RSS). The number of models were determined subjectively using the trends of RSS and Akaike Information Criteria (AIC) over the number of clusters. In addition, the study investigated the presence of overfitting in the CLR models, using a procedure proposed by Brusco et al. (2008). In this current study, overfitting means that most of the variations in the dependent variable appears to be explained by the estimated model; however, the actual relationship between the dependent variable and some of the explanatory variables and/or the functional form of the model is not really captured. Overfitting typically is evidenced during validation when the model is used to estimate values for the dependent variable, using data that was not used for model development. Later in this paper, the section on Model Performance provides a rigorous explanation of a procedure to determine potential overfitting in a model.

To address some of the limitations of previous models, a mathematical programming framework within the CLR approach is proposed to determine simultaneously the optimal number of clusters, the assignment of segments into clusters, and the associated PPMs (Khadka and Paz, 2017b). In this study, the Bayesian Information Criteria (BIC) (Schwarz 1978) was used as the objective function. BIC penalizes more for the inclusion of additional parameters than does AIC (Kadane and Lazar 2004). On the other hand, several studies showed that the number of parameters in a model selected using AIC was overestimated (Geweke and Meese, 1981; Katz, 1981; Koehler and Murphree, 1988; Kadane and Lazar 2004).

BIC is one of the most popular log-likelihood-based information criteria used for model selection. As BIC is an increasing function of the error variance and free parameters to be estimated, minimizing BIC reduces unexplained variations in the dependent variable, the number of explanatory variables, or both (Uzoma and Jeremiah, 2016). In case of a large sample size,

BIC is consistent in the sense that the probability of the selected model being the true model approaches '1' (Rao and Wu 1989; Yang 2005; Maydeu-Olivares and García-Forero 2010; Vrieze 2012, Kim et al. 2012).

In addition, the proposed framework tests the significance of explanatory variables. To the best of the authors' knowledge, all the existing literature about pavement management and PPMs estimation using CLR suffers from the limitation that variables included in the PPMs are assumed to be significant. However, the effects of variables without any evidence of significance can affect clustering and regression analyses. Therefore, heterogeneous samples can be assigned together erroneously (Fowlkes et al. 1988); therefore, it becomes challenging to discover the underlying pavement clusters that exhibit similar performance behavior (Gupta and Ibrahim 2007).

This problem is illustrated in Figure 1, using data from the Pavement Management System (PMS) of the Nevada Department of Transportation (NDOT). In this example, 54 randomly selected pavement samples were considered. Each pavement sample was represented by a dependent variable, PSI, and two explanatory variables, Age and Average Daily Traffic (ADT).

The variables PSI and Age had a significant linear relationship ($p\text{-value} = 0.001$), as shown in Figure 1a. The estimated BIC and root mean square error (RMSE) for the model were 85 and 0.2916, respectively. However, the relationship between PSI and ADT was not clear, as shown in Figure 1b. The estimated BIC and RMSE for the model were 251 and 0.4572, respectively. When both Age and ADT were included in the model as explanatory variables, the estimated BIC was increased to 90, with a slight decrease in RMSE by 0.0003. Hence, if an irrelevant variable, ADT in this example, is included in a CLR analysis without checking its

significance, it increases the BIC. In addition, it causes a loss of efficiency in the model. The estimated clustering and regression models may not capture the correct underlying relationships among the variables when a variable is included in the model without sufficient evidence of its significance.

Assignment of pavement samples into clusters using predefined and fixed explanatory variables, instead of estimation, introduces bias into the statistical analysis (Gupta and Ibrahim 2007). The available data are not fully utilized for clustering because the performance behavior represented by historical PSI is ignored. In addition, clustering using explanatory variables that do not provide any information about the underlying clustering structure does not reveal the underlying cluster assignments.

A legitimate assignment of pavement samples into homogeneous clusters to minimize the estimation error can be obtained using the relevant explanatory variables that exhibit the strongest effects on the dependent variable (Fowlkes et al. 1988; Liu and Ong 2008; and Maugis et al. 2009). The strength of the effects of explanatory variables on the dependent variable often is assessed by comparing p-values with the desired level of significance (α). A p-value represents the significance of the estimated coefficient for an explanatory variable. If the p-value for an explanatory variable is greater than α , there is not enough evidence to claim that the estimated coefficient is likely to be different from zero. In other words, changes in the explanatory variable do not reflect changes in the dependent variable. Hence, such explanatory variables having p-values greater than the desired α usually are excluded from the model during model estimation process.

A variable selection procedure can be utilized to select the best subset of potential explanatory variables. This procedure must distinguish between relevant and irrelevant variables

in order to provide the best regression models. Typically, the fewest number of explanatory variables that sufficiently explain most of the variances in the dependent variable are selected as the best model specification. In terms of data analysis and statistics, numerous methodologies for variable selection are available in the literature (Thompson 1978; Tibshirani 1996; Baumann 2003; Efron et al. 2004; Mehmood et al. 2012; Brusco 2014). In this study, the All-Subset Regression procedure (Garside 1965; Gorman and Toman 1966; Hocking and Leslie 1967; Mallows 1973; Berk 1978; Efron et al. 2004) was used to select variables for CLR analysis. All $(2^P - 1)$ possible subsets of potential explanatory variables, P , were examined. BIC was used as a criterion for comparing models with different subsets of variables.

It is not recommended to use least squares estimation and variable selection techniques under the presence of multicollinearity (Gunst and Webster 1975). Strongly-correlated clustering variables may overweight one or more underlying constructs and produce loss in efficiency (Ketchen and Shook 1996). Typically, multicollinearity inflates the variance of regression parameters and makes correct identification of significant variables challenging (Abdul-Wahab et al. 2005; Dorman et al. 2013; Ohlemüller et al. 2008). However, strongly correlated variables may not be a problem in all cases (Harrell 2001). In addition, if the collinearity between two variables remains constant, their estimated parameters are likely to have low standard errors; the problem would be serious if the standard errors of the correlated variables are high (Washington et al. 2011). The best way to address multicollinearity is to conduct a carefully designed experiment that considers the trade-off between removing and keeping potential explanatory variables that are expected to cause multicollinearity. Judgement and iterations are required to determine the best model specification that minimizes the effects of multicollinearity (Washington et al. 2011).

This study investigated the effects of highly-correlated explanatory variables. The Variance Inflation Factor (VIF), used to examine potential issues due to multicollinearity (Marquardt 1970; Mansfield and Helms 1982), is defined as $1/(1 - R_i^2)$, where R_i^2 is the R^2 for an explanatory variable, X_i regressed on the remaining explanatory variables. When no explanatory variables are correlated, the VIF is equal to '1'. As the degree of collinearity increases, both the variance of regression coefficient and the VIF increase (Yoo et al. 2014). Tacq (1997) showed that large VIF is an indicator of multicollinearity. In general, a VIF greater than '10' is considered unacceptable (Neter et al. 1996; Midi et al. 2010), even though no formal rule exists in the literature.

To avoid prespecifying the significance of potential explanatory variables, this paper proposes a comprehensive CLR framework that determines, simultaneously, the optimal number of pavement clusters, the assignment of segments into clusters, and the corresponding PPMs using only likely significant explanatory variables. The proposed framework simultaneously seeks for 1) the optimal number of clusters, 2) the combination of significant explanatory variables that provides the best goodness of fit, and 3) assigns segments into clusters. In the study, the likely significance of the explanatory variables was tested for each cluster model; hence, different clusters may include different significant explanatory variables.

Considering the simultaneous and extensive search for significant explanatory variables and the optimal number of clusters, the PPMs developed under the proposed framework were expected to provide superior explanatory power compared to existing approaches. The proposed framework was tested using pavement data from the entire State of Nevada. The results illustrate the advantage of solving simultaneously for the three types of parameters listed above.

196 METHODOLOGY

197 Problem formulation

198 This section describes a mathematical program that was formulated to describe the proposed
199 CLR problem. Among various pavement performance measures available in the literature, PSI is
200 a widely accepted measure that serves as a unified standard to measure pavement serviceability
201 (Shoukry et al. 1997; Terzi 2006; Attoh-Okine and Adarkwa 2013). PSI is understood easily by
202 both road users and legislators (Hudson et al. 2015). This study used PSI as the dependent
203 variable, y . Multiple linear regression PPMs were estimated with functional form expressed by:

$$204 \quad y_{it} = \beta_{0k} + \sum_{j=1}^J \beta_{jk} * x_{ijt} \quad (1)$$

205 The objective function was to minimize BIC, expressed as:

$$206 \quad Min. BIC = O + O * \ln(2\pi) + O * \ln\left(\frac{SSE}{O}\right) + (\delta + K - 1) * \ln(O) \quad (2)$$

207 where SSE is total sum of squared errors, expressed by:

$$208 \quad SSE = \sum_{k=1}^K \sum_{i=1}^I \sum_{t=1}^{T_i} (\beta_{0k} + \sum_{j=1}^J \beta_{jk} * x_{ijt} - y_{it})^2 * p_{ik} \quad \forall i \in I, j \in J, t \in T_i, k \in K \quad (3)$$

209 and the quantity $(\delta + K - 1)$ is the total number of free parameters to be estimated for K clusterwise
210 regression models (DeSarbo and Corn 1988). Intercepts (β_{0k}), coefficients for cluster-specific
211 significant explanatory variables (β_{jk}), the optimum number of clusters (K), and cluster
212 memberships (p_{ik}) were the decision variables to be determined. In addition, the proposed
213 mathematical programming included the following constraints:

214 Constraints for significant variables:

$$215 \quad \delta = \sum_k \sum_j v_{jk} \quad \forall j = 0, \dots, J, k \in K \quad (4)$$

$$216 \quad v_{jk} = \begin{cases} 1, & \text{if } \beta_{jk} \text{ is significant;} \\ 0, & \text{Otherwise} \end{cases} \quad \forall j = 0, \dots, J, k \in K \quad (5)$$

217 Membership constraints:

218
$$\sum_k p_{ik} = 1 \quad \forall i \in I, k \in K \quad (6)$$

219
$$p_{ik} = \begin{cases} 1, & \text{if sample } i \text{ is assigned to cluster } k; \\ 0, & \text{Otherwise} \end{cases} \quad \forall i \in I, k \in K \quad (7)$$

220 Constraints for feasible partitions:

221
$$C_k = \{i | p_{ik} = 1 \quad \forall i \in I, k \in K\} \quad (8)$$

222
$$C_{k'} \cap C_{k''} = \text{null} \quad \forall k' \neq k'', k' \text{ and } k'' \in K \quad (9)$$

223
$$\bigcup_{k \in K} C_k = I \quad (10)$$

224
$$\sum_{i \in C_k} T_i \geq n \quad \forall C_k \quad (11)$$

225 Constraints for range of clusters:

226
$$I \leq k \leq K_{max} \quad (12)$$

227
$$K_{max} = F(I, T_i, n) \quad (13)$$

228

229 The constraint expressed by (4) provided the total number of significant explanatory
230 variables, including intercepts for all the clusters. The sum of elements in each column of the
231 binary matrix, \mathbf{V} , of size $(J+1 \times K)$ provided the number of significant explanatory variables and
232 an associated intercept for a particular cluster. According to the constraint expressed by (5), the
233 element v_{jk} was equal to '1' if an estimated coefficient (β_{jk}) was significant in cluster k ;
234 otherwise, v_{jk} was '0' (Eq. 5). The significance of an explanatory variable as well as an intercept
235 was determined by using the p-value of its estimated regression coefficient.

236 Constraints expressed by (6) and (7) ensured that a pavement sample was assigned
237 exclusively to a single cluster. A binary indicator variable, p_{ik} , was used to define the

membership of a sample. Indicator p_{ik} equaled '1' if and only if a pavement sample i belonged to cluster k . Otherwise, p_{ik} was '0'.

The feasibility of the resulting clustering was guaranteed by constraints expressed by (8) - (11). Constraints expressed by (8) – (10) prevented the overlap of members among clusters; that is, pavement samples were divided exclusively into K clusters. Constraint (11) warranted that the number of observations for each cluster was no less than the minimum number of observations, n , in order to obtain the statistically reliable estimation of coefficients.

Constraints expressed by (12) and (13) were used to prevent a search beyond a feasible number of clusters. If the pavement sample had more than n observations, the sample alone could form a cluster. In reality, none of the pavement samples had more than n observations. Hence, samples were grouped into clusters to provide enough observations. All observations of a sample needed to be assigned to the same cluster.

The constraint expressed by (13) denoted the maximum number of feasible clusters. A procedure to calculate this maximum number was denoted by function F (Khadka et al., 2017). The procedure iteratively searched for the best combinations of the pavement samples to form a cluster such that each cluster had the required minimum number of observations. In the first step, it searched pavement samples with n or more observations. In this case, each pavement sample could form a cluster and was assigned to an individual cluster. Once all such cases were searched, the procedure searched two or more pavement samples, where a total number of observations equaled to n . In this step, all possible combinations of pavement samples with a total number of observations equal to n were searched to find the maximum number of combinations. No sample could be assigned to more than one cluster. After assigning all possible

combinations, the algorithm seeks for the combination(s) of samples having the minimal number of extra observations in each cluster.

Solution to the mathematical program

This study integrated Simulated Annealing (SA) (Krickpatrick et al. 1983; Černý, 1985) with Ordinary Least Square (OLS) to solve the proposed mathematical program, which is described as follows by means of algorithmic steps and a discussion regarding the details. SA was chosen because it provides a probabilistic mechanism to seek a global optimum in a large search space that involves discrete variables, such as cluster membership. Thus, SA was used to determine the cluster memberships (p_{ik}) of the pavement samples. For each accepted cluster, the VIF for all explanatory variables were calculated as discussed in the introduction. Highly correlated explanatory variables that had VIFs greater than a predefined limiting VIF were excluded. All-subset regressions were utilized to find the best model and to estimate the associated regression coefficients (β_{jk}). BIC and the level of significance, α , were used as the criteria to select the best model. Hence, selected models included only significant explanatory variables at a given α .

The algorithm utilized to solve the proposed mathematical program is described as follows, and is illustrated in Figure 2.

Step 1. Set $K = 2$, $BIC_{min} = \text{infinity}$, and $N = 1$.

Step 2. Calculate the maximum number of feasible clusters, K_{max} , utilizing function F, described above, as part of the constraint expressed by (13).

Step 3. For a given K , randomly assign pavement samples into clusters using the following steps:

281 Step 3.1. Generate a random number $u \sim U(1, K)$ and assign it to each of the pavement
282 sample used for the estimation of CLR models. When a sample is assigned to a
283 cluster, all observations associated with that sample are assigned to this cluster.

284 Step 3.2. Find the total number of observations assigned to each of the clusters, (i.e., 1 to
285 K).

286 Step 3.3. If all the clusters have at least n observations, then go to Step 4; otherwise, repeat
287 Steps 3.1 and 3.2 until all the clusters have at least n observations. Let $C_K^N \forall 1 \leq$
288 $k \leq K$ be the valid initial clusters.

289 Step 4. All-subset regression: Repeat the following steps for all K clusters.

290 Step 4.1. Calculate VIF for all explanatory variables. Exclude variables that have $VIF >$
291 VIF_{max} . Let \hat{J} be the set of explanatory variables with $VIF < VIF_{max}$.

292 Step 4.2. Generate all possible $2^{|\hat{J}|} - 1$ subsets of \hat{J} .

293 Step 4.3. Estimate β_{jk} for all subsets, using OLS, and calculate BIC for all the models.

294 Step 4.4. Rank models in ascending order, using BIC .

295 Step 4.5. Select the model that has the minimum BIC and all significant explanatory
296 variables with $p\text{-value} < \alpha$.

297 Step 5. Calculate the total number of free parameters to be estimated, $(\delta + K - 1)$. Calculate BIC
298 using Eq. 2.

299 Step 6. Using the following steps, generate valid neighborhood clusters near to the previous
300 ones.

301 Step 6.1. Select N_{ps} pavement samples randomly. For each of the selected samples, assign a
302 new membership by generating a random number $u_1 \sim U(1, K)$. If the new
303 membership is the same as previously, regenerate a random number $u_2 \sim U(1, K)$

304 until a different outcome is obtained. Repeat this process until the memberships of
305 all selected samples are different from those previously assigned.

306 Step 6.2. If all clusters have at least n observations, go to Step 7; otherwise, repeat Step 6.1.
307 until all clusters have at least n observations. Let C_K^{N+1} be the new set of valid
308 neighborhood clusters.

309 Step 7. For C_K^{N+1} , repeat Step 4 to estimate β_{jk} for all K clusters.

310 Step 8. Calculate the total number of free parameters to be estimated, $(\delta+K-1)$, and evaluate
311 BIC_K^{N+1} , using the Eq. 2.

312 Step 9. Search of a solution.

313 Step 9.1. Calculate $\Delta BIC = BIC_K^{N+1} - BIC_K^N$.

314 Step 9.2. Check the following two conditions:

315 a. If $\Delta BIC < 0$, accept current set of clusters, C_K^{N+1} , and the corresponding β_{jk} ; go
316 to Step 10, otherwise, go to Step b.

317 b. Generate a random number $u \sim U(0,1)$. Calculate the acceptance probability,
318 $p_{accept} = \exp\left(\frac{-\Delta BIC}{B \cdot T}\right)$, where B is the Boltzmann's constant. If $p_{accept} > u$,
319 accept the current set of clusters, C_K^{N+1} , and the corresponding β_{jk} . Go to Step 10;
320 otherwise, return to Step 6.

321 Step 10. Counter and temperature update.

322 Step 10.1. Repeat Steps 6 to 9 for N_{max} times.

323 Step 10.2. If $\theta < \theta_{min}$, stop the algorithm. Otherwise, reduce the temperature by
324 multiplying the current temperature by λ , set $N=1$, and go to Step 6.

325 Step 11. Stopping criteria.

326 Step 11.1. Update BIC_{min} with the smallest between the values obtained in Step 10 and the

current BIC_{min} . Set $K_{optimal} = K$.

Step 11.2. Repeat Steps 3 to 10 for $K_{max} - 1$ times.

To seek a global solution, this algorithm used a probabilistic approach during the search process. The initial solution was improved repetitively by making small changes until a better solution was obtained (Sridhar and Rajendran 1993; Johnson et al. 1989). The algorithm accepted better solutions as well as non-improving (worse) solutions at a certain probability (Dolan et al. 1989; Rutenbar 1989; Aarts et al. 2005). This probability decreased continuously over iterations, and depended on 1) the difference between the BICs of the current solution and a newly selected solution, and 2) the current temperature (Nikolaev and Jacobson 2010).

Initially, at a high temperature, the algorithm accepted worse solutions, which caused larger increments in BIC. As the temperature went down, the algorithm accepted worse solutions with relatively smaller increments in BIC. Finally, when the temperature dropped to zero, the algorithm no longer accepted worse solutions. This enabled occasional ‘uphill’ moves that helped the algorithm to escape from the local minima. Thus, the algorithm tried to explore the entire solution space to seek for a global solution (Dolan et al. 1989). Previous studies have shown that the algorithm converged to a global minimum when an infinitely slow cooling schedule was utilized (Román-Román et al. 2012).

Application of CLR Models

Luo and Chao (2008) proposed a procedure to apply CLR models to estimate pavement conditions. However, the proposed procedure applies only for cases when pavement age is the only independent variable. In addition, the procedure cannot be used to estimate the condition of a pavement sample that was not used to develop the CLR model. In other words, the procedure

cannot be used to determine the cluster memberships of the pavement samples that are not included in the estimation process.

To address this issues, this study proposed a heuristic to closely assign the cluster membership to a pavement sample. It was assumed that the new sample had observations for all the explanatory variables included in the estimated CLR models as well as the dependent variable (i.e. PSI), for at least one year. The following procedure could be used to estimate PSI using CLR models and the observations for a pavement sample:

1. Estimate \widehat{PSI}_t^k separately for all T observations of a sample, using each of the K estimated CLR models.
2. Calculate the overall sum of squared error (SSE) for each of the models, $\sum_k \Delta PSI_t^k = \sum_k (\widehat{PSI}_t^k - PSI_t^k)^2$
3. The sample is assigned to the model associated with the least overall SSE.

EXPERIMENT AND RESULTS

Data

Experiments were performed using the Pavement Management System (PMS) of the Nevada Department of Transportation (NDOT). The data included condition monitoring and roadway inventory data collected throughout the entire State of Nevada. Potential explanatory variables used in this study could be divided as follows:

1. Continuous explanatory variables:
 - *age* - pavement age since the last M&R treatment;
 - *adt* - average daily traffic in one direction;
 - *trucks* - average daily trucks in one direction;

- *elevation* - midpoint elevation of a segment;
- *precip* - average annual precipitation (cm/yr);
- *min_temp* - minimum average annual temperature ($^{\circ}\text{C}$);
- *max_temp* - maximum average annual temperature ($^{\circ}\text{C}$);
- *wet_days* - total number of wet days in a year;
- *freeze_thaw* - total number of freeze-thaw cycles that a pavement experienced in a year;
- *rut_depth* - average ride rut depth (cm);

2. Categorical explanatory variables:

- Two dummy variables for the number of lanes were encoded as:
 - *lane* ≤ 2 was equal to '1' if the pavement sample had two or less lanes and zero otherwise, and
 - *lane* ≥ 3 was equal to '1' if the pavement sample had three or more lanes and zero otherwise.
- NDOT classifies pavement samples under
 - The Interstate Route (IR),
 - The National Highway System (NHS), or
 - The Surface Transportation Program (STP).

Two dummy variables, *nhs* and *stp*, were encoded as: *nhs* was equal to '1' if a segment belonged to the NHS; otherwise, *nhs* was equal to '0'. Similarly, *stp* was equal to '1' if a segment belonged to STP; otherwise, *stp* was equal to '0'.

- NDOT grouped its roadway network into five prioritization categories, 1- 5, using such factors as facility type and traffic volumes (NDOT, 2011). The type and

frequency of maintenance and rehabilitation (M&R) activities vary among these prioritization categories. Four dummy variables – *category=2*, *category=3*, *category=4*, and *category=5* – were encoded as:

- *category=2* was equal to ‘1’ if the pavement sample is under Prioritization Category 2, ‘0’ otherwise; and
- *category=3* was equal to ‘1’ if the pavement sample was under Prioritization Category 3, ‘0’ otherwise.

The same approach was used for the other three dummy variables.

- Code of Federal Regulations (CFR) Title 23 part 470 mandates state agencies to identify the functional class of roads and streets. NDOT divided its roadway network into seven functional classes: (i) Interstate and Highway, (ii) Other Freeways and Expressway, (iii) Principal Arterial-Other, (iv) Minor Arterial, (v) Major Collector, (vi) Minor Collector, and (vii) Local. Six dummy variables – *f_class=2*, *f_class=3*, *f_class=4*, *f_class=5*, *f_class=6* and *f_class=7* – were encoded as follows:

- *f_class=2* was equal to ‘1’ if the pavement sample was an Interstate and Highway, ‘0’ otherwise;
- *f_class=3* was equal to ‘1’ if the pavement sample was classified as Other Freeways and Expressway, ‘0’ otherwise.

The same approach was used for the other four dummy variables.

A total of 4,138 samples – including 14,638 observations from 2001 to 2010 and 3,005 observations from 2011 and 2012 – were available for model estimation and validation, respectively. Table 1 illustrates a subset of data used in the experiments.

Estimation parameters

The existing literature does not provide hard-and-fast rules to define the limiting VIF beyond the one that indicates a serious multicollinearity problem (Petraitis et al. 1996). Many studies (Myers 1990; Neter et al. 1996; Chatterjee and Hadi 2000) suggested that a multicollinearity problem was serious if the VIF was greater than 10. In this study, all explanatory variables with $VIF > 10$ were excluded from the final models. Other estimation parameters that were required were set by using previous experience (Paz et al. 2015a; Paz et al. 2015b) and sensitivity analyses. Table 2 provides the parameter values used in this study.

Experiment results and discussion

Function F in the constraint expressed by (13) was used to determine the maximum number of feasible clusters for the dataset used in this study. The algorithm found that 16 was the maximum number of feasible clusters that fulfilled the requirements imposed by the constraints for feasible partitions.

The solution algorithm proposed in the section, Solution to the Mathematical Program, sought for the optimum number of clusters by exploring each of all feasible clusters (i.e., $K = 2$ to 16). Thus, the algorithm determined that 6-cluster CLR models provided the optimum solution with the lowest BIC. Figure 3a shows the BIC trend over the number of clusters that were considered in this experiment. Figure 3b shows the convergence of the objective function, BIC, over iterations when the six-cluster CLR models were used. After 983 iterations, the BIC decreased from the initial value of 9,283 to the final value of 6,443, with an improvement of 31%.

Coefficients for the variables, *trucks* and *freeze_thaw*, were positive. This is counter-intuitive because a pavement deteriorates faster when it is subjected to heavy trucks and frequent

freeze-thaw cycles. Hence, additional data analysis was performed to investigate the data quality. The analysis showed average positive trends of PSI for these variables; this could be because pavements having a larger number of trucks and freeze-thaw cycles often are designed to have stronger pavement structures, and are continuously maintained. This research did not use any explanatory variable that relates PSI to pavement structure. Hence, *trucks* and *freeze_thaw*, which were likely to be positively correlated with missing information, such as pavement structure, may have captured this hidden effect. There could be other reasons for the positive coefficients for *trucks* and *freeze-thaw*; however, this investigation did not find enough evidence to justify these positive trends. Hence, these two variables were excluded from the models, and new model parameters were estimated. The effect of these two variables was discussed in Khadka and Paz (2017a). Future research is recommended to investigate this issue. Table 3 provides the estimated parameters for 6-cluster models.

This study used a 5% significance level. Results showed that seven explanatory variables – *elevation*, *precip*, *min_temp*, *max_temp*, *wet_days*, *nhs*, and *stp* – were not included in any of the final estimated 6-cluster models. As the constraints for significant variables were imposed, the algorithm excluded these seven variables because they were either associated with high VIF, causing multicollinearity, or were statistically insignificant. Hence, the resultant models only had statistically significant explanatory variables. Table 4 shows the binary matrix, *V*, associated with the 6-cluster models estimated in this study. Each ‘1’ indicates a ‘significant’ variable for a particular cluster; ‘0’ indicates otherwise.

Table 3 also includes the VIFs of the significant explanatory variables. All the VIF values were less than five, which indicated that the associated explanatory variables in each model did

not have strong correlations among each other. Hence, the resultant models were free from serious multicollinearity problems.

The six models included different significant explanatory variables. In addition, the common variables had different estimated coefficients. These differences indicated that pavement samples across the clusters were heterogeneous by the effect of explanatory variables, and exhibited different types of performance behavior. For example, the samples exhibited different deterioration rates as they got older. The estimated coefficients for *age* were -0.039 and -0.022 for Clusters #1 and #2, respectively. However, pavement samples in Clusters #1 and #2 performed similarly with respect to traffic-loading conditions. That is, the estimated coefficients for *adt* in Clusters #1 and #2 were -0.013 and -0.012, respectively.

Only four variables – *intercept*, *age*, *adt*, and *rut_depth* – were common for all six models; and all of them had a negative sign, except for the intercept. All the estimated intercept values were realistic. The PSI of a newly constructed pavement was about 4.5 (Christopher et al. 2006). However, the intercepts differed across the models. The negative signs of *age* and *adt* indicated that the conditions deteriorated when a pavement became older and was subjected to greater traffic loadings, respectively. Similarly, the PSI of a pavement sample decreased as rutting along the pavement became deeper.

It was observed that Clusters #2 to #5, which had as significant variables *category=2*, *category=3*, *category=4*, and *category=5*, also had variables *lane*≤2 and *lane*≥3 as significant. In contrast, the variable *f_class* was not significant in these clusters. The estimated coefficients of the variables *category=2*, *category=3*, *category=4*, and *category=5* were negative, and the coefficient increased as the category level went up. This indicated that the average PSIs in these four category levels (i.e., from 2 to 5) were smaller than for that of Category 1, and decreased as

the level went up. This was expected, because NDOT assigned the highest priority – in terms of maintaining good conditions – to the roadway segments identified as Category 1 and the lowest priority to the roadway segments identified as Category 5 (NDOT 2011). The variable *f_class* was significant only in Clusters 1 and 6. The coefficients for all six classes were negative, except for the *f_class*=2 in Cluster 6. A positive sign indicated that the pavement samples classified as Class 2 had a higher average PSI than for the segments classified as Class 1. It also was observed that for both clusters, the coefficient increased as the class number went up, except for the *f_class*=7. A possible reason was that the estimation was based on only 44 observations (Functional Class 7), which might not represent actual conditions.

Model performance

In CLR, minimizing overall SSE translates the maximization of variations in the dependent variable explained by clustering process and regression models (Brusco et al. 2008). CLR does not differentiate between the variations explained by the clustering process and variations explained by regression models. Hence, in some cases, variation in the dependent variable could be minimized by the clustering process even if variations explained by the regression models are small. This creates a potential for overfitting the data in cases when regression relationships are not strong.

Brusco et al. (2008) proposed a procedure to diagnose the presence of overfitting in the resultant CLR models. Five different metrics were calculated for the optimum 6-cluster models, and are included in Table 5. The results showed that the between-clusters sum of squares (BCSS), which represent the variations explained by the clustering process, was equal to '4', which is less than 1% of the total sum of squares (TSS). The sum of squares due to regression (SSR) was equal to 1,130, which was 47% of the within-clusters sum of squares (WCSS). The

WCSS represents the sum of the variations across clusters, which is the sum of SSE and SSR. This indicated that there was no overfitting, as most of the variations in PSI was explained by within-cluster regressions. However, SSE accounted for 53% of the TSS, which indicated that the resultant models had relatively high errors, possibly due to the nature of the data. In addition, the estimated linear function might not have been the best to use in order to explain the pavement deterioration.

The prediction accuracy of the models was evaluated by calculating the RMSE, the normalized root-mean-square error (NRMSE), and the mean absolute error (MAE), using (14), (15), and (16), respectively:

$$RMSE = \sqrt{\sum_i^\eta (y_{it} - \hat{y}_{it})^2 / \eta} \quad (14)$$

$$NRMSE = \frac{RMSE}{y_{max} - y_{min}} \quad (15)$$

$$MAE = \frac{1}{\eta} \sum_1^\eta |y_{it} - \hat{y}_{it}| \quad (16)$$

where y_{it} = the observed PSI, \hat{y}_{it} = the predicted PSI, y_{max} = the maximum observed PSI, y_{min} = the minimum observed PSI, and η = the number of predictions. The estimated model coefficients were applied to the test dataset described in the Data section to estimate PSIs for 2011 and 2012. The overall RMSE, NRMSE, and MAE values for all the models were 0.47, 0.17, and 0.36, respectively. This indicated that the resultant models were robust.

In addition, to diagnose the variation in the prediction errors, the RMSE, NRMSE, and MAE were calculated separately for all six models. Table 6 provides the RMSE, NRMSE, and MAE values for all the models as well as the individual models. It was observed that the differences between RMSE and MAE values were approximately equal for all the models, which indicated that the prediction errors were well distributed among the clusters.

Figure 4a shows a scattered plot of predicted versus observed PSIs for 2011 and 2012. The degree of prediction error of the models was reflected by the relative positions of the data points from the 45^0 line. Data points above the 45^0 line were over-predicted, while those under the 45^0 line were under-predicted. Results indicated that the predicted PSIs ranged from 2.70 to 4.42, whereas the observed PSIs ranged from 1.64 to about 4.44. In particular, the CLR models overestimated PSIs that were at the lower end of the data. Possible reasons for overestimation could be that this study did not include any explanatory variables that captured the pavement structure. In addition, improvements by routine maintenance activities were ignored.

Figure 4b provides the percentages of observations that were within different ranges of error. For example, about 74% of the total number of predictions were contained within a $\pm 15\%$ range of error. Figure 5 shows individual scattered plots of predicted versus observed PSIs for all six models.

CONCLUSIONS AND RECOMMENDATIONS

In this paper, a comprehensive mathematical program is proposed to estimate PPMs that minimize the estimation error by simultaneously finding 1) the optimum number of pavement clusters, 2) cluster memberships of the samples, 3) cluster-specific significant explanatory variables, and 4) regression coefficients. To solve the mathematical program, Simulated Annealing integrated with All-subset regression was implemented. The algorithm has the capability to identify potential explanatory variables that cause serious multicollinearity in a model.

VIF was used to measure the effect of multicollinearity in a model. In this study, multicollinearity was addressed using a traditional approach where correlated variables were removed one at a time until the effect of multicollinearity became minimal. However, a better

way to address multicollinearity is to consider the trade-off between removing and keeping potential explanatory variables that are expected to cause multicollinearity. Future research is recommended to integrate such an experiment in the CLR framework.

After addressing the multicollinearity issue, the proposed algorithm identified the relevant explanatory variables to be included in the models. All possible combinations of the explanatory variables were evaluated to select the best model for each cluster. Hence, the estimated CLR models included cluster-specific significant explanatory variables that were free from multicollinearity.

The algorithm explored all the feasible clusters that could be formed for the data used in the experiments, and found that 6-cluster models were the optimum solution. The algorithm determined the significant explanatory variables to be traffic-loading conditions of both ADT and the number of trucks, age, rut-depth, function class, prioritization category, freeze-and-thaw cycles, and the number of lanes. In the literature, all these variables were considered to be the most critical factors for pavement deterioration (Saraf and Majidzadeh 1992; Prozzi and Madanat 2004; Kim and Kim 2006; Salama et al. 2006). Both the magnitude and sign of the estimated regression coefficients were as expected, and were realistic. This indicates that the proposed algorithm was very effective when selecting the explanatory variables that were relevant.

The estimated CLR models first were analyzed to investigate the presence of overfitting, and the results showed that the models did not possess any overfitting issues. To investigate the predictive capability of the models, RMSE, NRMSE, and MAE were calculated for all the models as well as for individual models. The overall RMSE, NRMSE, and MAE values of 0.47, 0.17, and 0.36, respectively, indicated that the estimated models had small estimation errors. In addition, the results showed that both the differences between the RMSE and MAE values for all

six models were approximately equal, which indicated that the prediction error was well distributed among the models. Even so, the models still were associated with prediction errors.

The linear functional form used in this study did not exactly fit the data used in the experiments. Hence, it would be worth investigating the proposed methodology by using nonlinear relationships between pavement performance measures and multiple explanatory variables. Various forms of power and sigmoidal models (Sadek et al. 1996; Luo and Chou 2006; Zhang and Durango-Cohen 2014; and Chen and Mastin 2015) could be investigated.

Finally, the results indicated that each cluster had almost an equal number of members (i.e., pavement samples). However, it is unlikely that the underlying clusters had equally distributed pavement samples. An interesting aspect worthy of investigation would be to explore the likelihood of distribution of the pavement samples and the associated physical characteristics. Further investigation would be required to identify any dominant explanatory variables of the pavement samples that define a cluster.

This study also proposed a heuristic to assign cluster membership to a pavement sample. It was assumed that a new sample had observations for all explanatory variables included in the estimated CLR models as well as the dependent variable (i.e. PSI). Future research is recommended to develop a procedure to assign cluster membership to pavement samples that were not included during model estimation and lack data about the dependent variable.

The proposed algorithm was designed to search for a global minimum; however, a large amount of computational time is required. Another avenue for future research would be to develop faster and more efficient combinatorial algorithms that would guarantee global optimality.

597 **ACKNOWLEDGMENTS**

598 Many thanks to the Nevada Department of Transportation for providing the data that was used
599 for analysis, and to our Technical Writer at UNLV's Howard R. Hughes College of Engineering,
600 Mrs. Julie Longo, for her help reviewing this manuscript. Special thanks to Mr. Fabien Sortais
601 for his help with the implementation of the solution algorithm. The authors would like to thank
602 all the anonymous reviewers and editor for their comments that contributed to improving the
603 final version of the paper.

604 **NOTATION**

605 *The following symbols are used in this paper:*

606 I = Number of pavement samples in the network;

607 i = Subscript for a pavement sample in the network, $i \in I$;

608 T_i = Number of observation periods for a pavement sample i ;

609 t = Subscript for an observation period for a pavement sample i , $t \in T_i$;

610 O = Total number of observations = $\sum_i^I T_i \forall i \in I$;

611 J = Number of explanatory variables;

612 j = Subscript for an explanatory variable including an intercept, $j = 0, \dots, J$

613 x_{ijt} = Measurement of an explanatory variable j for a sample i at observation period t that is
614 assigned to a cluster $k \forall i \in I, j \in J, t \in T_i$;

615 y_{it} = Measurement of dependent variable for a sample i at observation period t that is assigned to
616 a cluster $k \forall i \in I, t \in T_i$;

617 K = Optimum number of clusters ($1 \leq k \leq K_{max}$);

618 k = Subscript for a cluster, $k \in K$;

619 K_{max} = Maximum number of potential clusters that could be formed using the given data;

620 n = Minimum number of observations required in a cluster;

621 C_k = Set of pavement samples that are assigned to cluster $k \forall k \in K$;

622 δ = Total number of significant explanatory variables including intercepts in all clusters;

623 v_{jk} = Binary indicator that represents significance of an explanatory variable including an

624 intercept in a cluster $k \forall j = 0, \dots, J, k \in K$;

625 p_{ik} = Cluster membership of a pavement sample i to a cluster $k, \forall i \in I, k \in K$;

626 β_{jk} = Estimated regression coefficient for an explanatory variable j including an intercept in

627 cluster $k \forall j = 0, \dots, J, k \in K$;

628 REFERENCES

- 629 Aarts, E., Korst, J. and Michiels, W. (2005). "Simulated Annealing." *Search Methodologies:*
- 630 *Introductory Tutorials in Optimization and Decision Support Techniques*, Springer US,
- 631 187–210, DOI: 10.1007/0-387-28356-0_7.
- 632 Abdul-Wahaba, S. A., Bakheitb, C. S. and Al-Alawia, S. M. (2005). "Principal component and
- 633 multiple regression analysis in modelling of ground-level ozone and factors affecting its
- 634 concentrations." *Environmental Modelling & Software*, 20(10), 1263–1271.
- 635 Attoh-Okine, N. and Adarkwa, O. (2013). "Pavement Condition Surveys–Overview of Current
- 636 Practices." [www.sites.udel.edu/dct/files/2013/10/Rpt-245-Pavement-Condition-Okine-](http://www.sites.udel.edu/dct/files/2013/10/Rpt-245-Pavement-Condition-Okine-DCTR422232-1pzk0uz.pdf)
- 637 [DCTR422232-1pzk0uz.pdf](http://www.sites.udel.edu/dct/files/2013/10/Rpt-245-Pavement-Condition-Okine-DCTR422232-1pzk0uz.pdf) (January 2016).
- 638 Baumann, K. (2003). "Cross-validation as the objective function for variable-selection
- 639 techniques." *TrAC Trends in Analytical Chemistry*, 22(6), 395–406, DOI:
- 640 10.1016/S0165-9936(03)00607-1.
- 641 Berk, K. N. (1978). "Comparing Subset Regression Procedures." *Technometrics*, 20(1), 1–6.

642 Brusco, M. J. (2014). "A comparison of simulated annealing algorithms for variable selection in
643 principal component analysis and discriminant analysis." *Computational Statistics &*
644 *Data Analysis*, 77, 38–53.

645 Brusco, M. J., Cradit, J. D., Steinley, D. and Fox, G. L. (2008). "Cautionary Remarks on the Use
646 of Clusterwise Regression." *Multivariate Behavioral Research*, 43(1), 29–49.

647 Carbonnea, R. A., Caporossi, G. and Hansen, P. (2011). "Globally optimal clusterwise regression
648 by mixed logical-quadratic programming." *European Journal of Operational Research*,
649 212(1), 213–222.

650 Černý, V. (1985). "A Thermodynamical Approach to the Travelling Salesman Problem; An
651 Efficient Simulation Algorithm." *J. of Optimization Theory and Applic.* 45, 41-55.

652 Chatterjee, S. and Hadi, A. S. (2000). *Regression analysis by example*, John Wiley and Sons,
653 New York, USA.

654 Chen, D. and Mastin, N. (2015). "Sigmoidal models for predicting pavement performance
655 conditions." *J. Perform. Constr. Facil.*, 30(4). DOI:10.1061/(ASCE)CF.1943-
656 5509.0000833.

657 Christopher, B. R., Schwartz, C. and Boudreau, R. (2006). "Geotechnical Aspects of
658 Pavements." *Report No. FHWA NHI-05-037*, U.S. Department of Transportation,
659 Washington, D.C.

660 Davies, R. M. and Sorenson, J. (2000). "Pavement preservation: Preserving our investment in
661 highways." *Public Roads*, 63(2), 63–69.

662 DeSarbo, W. S. and Corn, W. L. (1988). "A Maximum Likelihood Methodology for Clusterwise
663 Linear Regression." *Journal of Classification*, 5(2), 249–282.

664 DeSarbo, W. S., Oliver, R. L. and Rangaswamy, A. (1989). "A Simulated Annealing
665 Methodology for Clusterwise Linear Regression." *Psychometrika*, 54(4), 707–736.

666 Dolan, W. B., Cummings, P. T. and LeVan, M. D. (1989). "Process optimization via simulated
667 annealing: Application to network design." *AIChE Journal*, 35(5), 725–736, DOI:
668 10.1002/aic.690350504.

669 Dormann, C. F., Elith, J., Bacher, S., Buchmann, C., Carl, G., Carré, G., Marquéz, J. R. G.,
670 Gruber, B., Lafourcade, B., Leitão, P. J. and Münkemüller, T. (2013). "Collinearity: a
671 review of methods to deal with it and a simulation study evaluating their performance."
672 *Ecography*, 36(1), 27-46.

673 Efron, B., Hastie, T., Johnstone, I. and Tibshirani, R. (2004). "Least Angle Regression." *The*
674 *Annals of Statistics*, 32(2), 407–499.

675 Fowlkes, E. B., Gnanadesikan, R. and Kettenring, J. R. (1988). "Variable Selection in
676 Clustering." *Journal of Classification*, 5(2), 205–228.

677 Garside, M. J. (1965). "The Best Subset in Multiple Regression Analysis." *Applied Stat. Journ.*
678 *of the Royal Statist. Society, Series C.*, 14(2), 196–200.

679 Geweke, J. F., and Meese, R. A. (1981). "Estimating Regression Models of Finite but Unknown
680 Order." *International Economics Review*, 22, 55–70.

681 Gorman, J. W. and Toman, R. J. (1966). "Selection of Variables for Fitting Equations to Data."
682 *Technometrics*, 8(1), 27–51, DOI: 0.1080/00401706.1966.10490322.

683 Gunst, R. F. and Webster, J. T. (1975). "Regression analysis and problems of multicollinearity."
684 *Communications in Statistics*, 4(3), 277–292, DOI: 10.1080/03610927308827246.

685 Gupta, M. and Ibrahim, J. G. (2007). "Variable selection in regression mixture modeling for the
686 discovery of gene regulatory networks." *Journal of the American Statistical Association*,
687 102(479), 867–880.

688 Hajj, E. Y., Loria, L. and Sebaaly, P. E. (2010). "Performance Evaluation of Asphalt Pavement
689 Preservation Activities." *Transportation Research Record: Journal of the Transportation*
690 *Research Board*, 2150, 36–46.

691 Harrell, F. E. (2001). *Regression Modeling Strategies: with Applications to Linear Models,*
692 *Logistic Regression, and Survival Analysis (Second Ed.)*, Springer, Cham, Heidelberg,
693 New York Dordrecht, London.

694 Highway Research Board. (1962). "The AASHO road test." *Special Rep. No. 61A-E*, National
695 Academy of Science, National Research Council, Washington, DC.

696 Hocking, R. R. and Leslie, R. N. (1967). "Selection of the Best Subset in Regression Analysis."
697 *Technometrics*, 9(4), 531–540.

698 Hudson, W. R., Haas, R. and Perrone, E. (2015). "Measures of Pavement Performance must
699 consider the Road User." *Proc., 9th International Conference on Managing Pavement*
700 *Assets*, Alexandria, VA.

701 Johnson, D. S., Aragon, C. R., McGeoch, L. A. and Schevon, C. (1989). "Optimization by
702 simulated annealing: an experimental evaluation; part I, graph partitioning." *Operations*
703 *research*, 37(6), 865–892.

704 Joseph B. Kadane, J. B. and Lazar, N. A. (2004). "Methods and Criteria for Model Selection."
705 *Journal of the American Statistical Association*, 99(465) 279-290.

706 Katz, R. W. (1981). "On Some Criteria for Estimating the Order of a Markov Chain."
707 *Technometrics*, 23, 243–249.

708 Ketchen, D. J. and Shook, C. L. (1996). "The Application of Cluster Analysis in Strategic
709 Management Research: An Analysis and Critique." *Strategic Management Journal*,
710 17(6), 441–458.

711 Khadka, M. and Paz, A. (2017a). "Limitations of Existing Pavement Performance Models and a
712 Potential Solution." *World Conference on Pavement and Asset Management*, Baveno,
713 Italy.

714 Khadka, M., & Paz, A. (2017b). Estimation of optimal pavement performance models for
715 highways. Tenth International Conference on the Bearing Capacity of Roads, Railways
716 and Airfields. Athens, Greece.

717 Khadka, M., Paz, A., Cristian, A., and Hale, D. K. (2017). "Simultaneous Generation of
718 Optimum Pavement Clusters and Associated Performance Models." Manuscript
719 submitted for publication in *Transportmetrica A: Transport Science*. Under review.

720 Kim, S. and Kim N. (2006). "Development of performance prediction models in flexible
721 pavement using regression analysis method." *KSCE J. of Civil Engineering*, 10(2), 91–
722 96.

723 Kim, Y., Kwon, S., and Choi, H. (2012). "Consistent Model Selection Criteria on High
724 Dimensions." *Journal of Machine Learning Research*, 13(1), 1037-1057.

725 Kirkpatrick, S., Gelatt, C. D. and Vecchi, M. P. (1983). "Optimization by Simulated Annealing."
726 *Science, New Series*, 220(4598), 671-680.

727 Koehler, A. B. and Murphree, E. S. (1988). "A Comparison of the Akaike and Schwarz Criteria
728 for Selecting Model Order." *Applied Statistics*, 37, 187-19.

729 Labi, S. and Sinha, K. C. (2003). "Life-cycle evaluation of highway pavement preventive
730 maintenance." [CD-ROM], 82nd annual meeting of the Transportation Research Board,

731 National Research Council, Washington DC.

732 Lau, K., Leung, P. and Tse, K. (1999). "A mathematical programming approach to clusterwise
733 regression model and its extensions." *European Journal of Operational Research*,
734 116(3), 640–652.

735 Liu, H. H. and Ong, C. S. (2008). "Variable selection in clustering for marketing segmentation
736 using genetic algorithms." *Expert Systems with Applications*, 34(1), 502–510.

737 Lu, H., Huang, S., Li, Y. and Yang, Y. (2014). "Panel Data Analysis Via Variable Selection and
738 Subject Clustering." *Data Mining for Services*, 3, Springer-Verlag, 31–76.

739 Luo, Z. and Chou, E. Y. J. (2006). "Pavement Condition Prediction Using Clusterwise
740 Regression." *Transportation Research Record: Journal of the Transportation Research*
741 *Board*, No. 1974, 70–77.

742 Luo, Z. and Yin, H. (2008). Probabilistic Analysis of Pavement Distress Ratings with the
743 Clusterwise Regression Method, *Transportation Research Record: Journal of the*
744 *Transportation Research Board*, No. 2084, 38–46.

745 Mallows, C. L. (1973). "Some Comments on Cp." *Technometrics*, 15(4), 661–675.

746 Mansfield, E. R. and Helms, B. P. (1982). "Detecting Multicollinearity." *The American*
747 *Statistician*, 36(3a), 158-160. DOI: 10.1080/00031305.1982.10482818.

748 Marquardt, D. W. (1970). "Generalized inverses, ridge regression, biased linear estimation, and
749 nonlinear estimation." *Technometrics*, 12(3), 591–612.

750 Maugis, M., Celeux, G. and Martin-Magniette, M. L. (2009). "Variable Selection for Clustering
751 with Gaussian Mixture Models." *Journal of the International biometric society*, 65(2),
752 701-709.

753 Maydeu-Olivares, A. and García-Forero, C. (2010). “Goodness-of-fit testing.” *International*
754 *Encyclopedia of Education*, 7, 190–196.

755 Mehmood, T., Liland, K. H., Snipen, L. and Sæbø, S. (2012). “A review of variable selection
756 methods in Partial Least Squares Regression.” *Chemometrics and Intelligent Laboratory*
757 *Systems*, 118, 62–69.

758 Midi, H., Sarkar, S. K. and Rana, S. (2010). “Collinearity diagnostics of binary logistic
759 regression model.” *Journal of Interdisciplinary Mathematics*, 13(3), 253–267.

760 Myers, R.H. (1990). *Classical and Modern Regression with Applications*, 2nd edition, PWS
761 Kent, Boston, MA.

762 Neter, J., Kutner, M. H., Nachtsheim, C. J. and Wasserman, W. (1996). *Applied linear statistical*
763 *models*, Irwin, Chicago, Illinois, USA.

764 Nevada Department of Transportation (2011). *Pavement Management System Overview*,
765 Material Division, Nevada Department of Transportation, USA.

766 Nikolaev A. and Jacobson S. (2010). “Simulated annealing.” *Handbook of Metaheuristics*,
767 *International Series in Operations Research and Management Science*, 146, Springer,
768 Berlin, 1–39, DOI: 10.1007/978-1-4419-1665-5_1.

769 Ohlemuller, R., Anderson, B. J., Araujo, M. B., Butchart, S. H., Kudrna, O., Ridgely, R. S., and
770 Thomas. C. D. (2008). “The coincidence of climactic and species rarity: high risk to
771 small range species from climate change.” *Biology Letters*, 4, 568–572.

772 Park, Y. W., Jiang, Y., Klabjan, D. and Williams, L. (2015). “Algorithms for Generalized
773 Cluster-wise Linear Regression.” <http://www.dynresmanagement.com/publications>
774 (January 2016).

775 Paz, A., Molano, V. and Sanchez, M. (2015a). "Holistic Calibration of Microscopic Traffic
 776 Flow Models: Methodology and Real World Application Studies." *Engineering and*
 777 *Applied Sciences Optimization: Dedicated to the memory of Professor M.G. Karlaftis,*
 778 38, Ed. 1. Springer International Publishing.

779 Paz, A., Molano, V., Martinez, E., Gaviria, C. and Arteaga, C. (2015b). "Calibration of Traffic
 780 Flow Models Using a Memetic Algorithm." *Transportation Research Part-C: Emerging*
 781 *Technologies*, 55, 432–443.

782 Petraitis, P. S., Dunham, A. E. and Niewiarowski, P. H. (1996). "Inferring multiple causality: the
 783 limitations of path analysis." *Functional Ecology*, 10(4), 421–431.

784 Prozzi, J. A. and Madanat, S. M. (2004). "Development of pavement performance models by
 785 combining experimental and field data." *J. of Infrastructure Systems*, 10(1), 9–22.

786 Rao, C. R. and Wu, Y. (1989). "A strongly consistent procedure for model selection in a
 787 regression problem." *Biometrika*, 76(2), 369–374.

788 Román-Román, P., Romero, D., Rubio, M. A. and Torres-Ruiz, F. (2012). "Estimating the
 789 parameters of a Gompertz-type diffusion process by means of Simulated Annealing."
 790 *Applied Mathematics and Computation*, 218(9), 5121–5131.

791 Rutenbar, R.A. (1989). "Simulated Annealing Algorithms: An Overview." *IEEE Circuits and*
 792 *Devices Magazine*, 5(1), 19–26.

793 Sadek, A. W., Freeman, T. E. and Demetsky, M. J. (1996). "Deterioration prediction modeling of
 794 Virginia's interstate highway system." *Transportation Research Record: Journal of the*
 795 *Transportation Research Board*, No. 1524, 118–129.

796 Salama, H., Chatti, K. and Lyles, R. (2006). "Effect of Heavy Multiple Axle Trucks on Flexible
797 Pavement Damage Using In-Service Pavement Performance Data." *J. Transp. Eng.*,
798 132(10), 763-770.

799 Saraf C. L. and Majizzadeh, K. (1992). "Distress prediction models for a network level PMS."
800 *Transportation Research Record: Journal of the Transportation Research Board*, No.
801 1344, 38–48.

802 Schlittgen, R. (2011). "A weighted least-squares approach to clusterwise regression." *Advances*
803 *Statistical Analysis*, 95(2), 205–217.

804 Schwarz, G. (1978). "Estimating the dimension of a model." *Annals of Statistics*, 6(2), 461–464.

805 Shoukry, S. N., Martinelli, D. R. and Reigle, J. A. (1997). "Universal Pavement Distress
806 Evaluator Based on Fuzzy Sets." *Transportation Research Record: Journal of the*
807 *Transportation Research Board*, No. 1592, 180–186.

808 Spath, H. (1979). "Algorithm 39: Clusterwise linear regression." *Computing*, 22(4), 367–373.

809 Sridhar, J. and Rajendran, C. (1993). "Scheduling in a cellular manufacturing system: a
810 simulated annealing approach." *International Journal of Production Research*, 31(12),
811 2927-2945, DOI: 10.1080/00207549308956908

812 Tacq. J. (1997). *Multivariate analysis techniques in social science research: From problem to*
813 *analysis*, Sage Publications, London.

814 Tan, T., Suk, H. W., Hwang, H. and Lim, J. (2013). "Functional fuzzy clusterwise regression
815 analysis." *Adv. Data Anal. Classif.*, 7(1), 57–82.

816 Terzi, S. (2006). "Modeling the Pavement Present Serviceability Index of Flexible Highway
817 Pavements Using Data Mining." *Journal of Applied Sciences*, 6(1), 193–197.

818 Thompson, M. L. (1978). "Selection of Variables in Multiple Regression: Part I. A Review and
819 Evaluation." *International Statistical Review*, 46(1), 1–19, DOI: 10.2307/1402505.

820 Tibshirani, R. (1996). "Regression shrinkage and selection via the lasso." *J. R. Statist. Soc. B*, 58,
821 267–288.

822 Uzoma, U. and Jeremiah, O. O. (2016). "An Alternative Approach to AIC and Mallow's Cp
823 Statistic-Based Relative Influence Measures (RIMS) in Regression Variable Selection."
824 *Open Journal of Statistics*, 6(1), 70-75, DOI: 10.4236/ojs.2016.61009

825 Vrieze, S. I. (2012). "Model selection and psychological theory: A discussion of the differences
826 between the Akaike Information Criterion (AIC) and the Bayesian Information Criterion
827 (BIC)." *Psychol Methods*, 17(2), 228–243.

828 Washington, S. P., Karlaftis, M. G., and Mannering, F. L. (2011). *Statistical and Econometric*
829 *Methods for Transportation Data Analysis (Second Ed.)*, Chapman Hall/CRC, Boca
830 Raton, FL.

831 Wedel, M. and Steenkamp, J. (1989). "Fuzzy clusterwise regression approach to benefit
832 segmentation." *Int. J. Res. Mark.*, 6(4), 241–258.

833 Yang, Y. (2005). "Can the strengths of AIC and BIC be shared? A conflict between model
834 identification and regression estimation." *Biometrika*, 92(4), 937–950.

835 Yoo, W., Mayberry, R., Bae, S., Singh, K., (Peter) He, Q. and Lillard, J. W. (2014). "A Study of
836 Effects of MultiCollinearity in the Multivariable Analysis." *Int J Appl Sci Technol.*, 4(5),
837 9–19.

838 Zhang, W. and Durango-Cohen, P. (2014). "Explaining Heterogeneity in Pavement
839 Deterioration: Clusterwise Linear Regression Model." *J. Infrastruct. Syst.*, 20(2). DOI:
840 10.1061/(ASCE)IS.1943-555X.0000182.

841 Zhen, Z., Yan, L. and Nan, K. (2012). "Clusterwise linear regression with the least sum of
842 absolute deviations - An MIP approach." *Int. J. Oper. Res.*, 9(3), 62172.

843

844 **Table 1.** A Subset of Data used in the Experiments

Sample ID	1				2			
Year	2001	2002	2003	2004	2001	2002	2003	2004
<i>psi</i>	3.82	3.73	3.71	3.62	3.96	3.88	3.86	3.53
<i>age</i>	0	1	2	3	0	1	2	3
<i>adt</i>	725	825	950	950	725	825	950	950
<i>trucks</i>	20	20	19	20	20	20	19	20
<i>elevation</i>	4750	4750	4750	4750	4750	4750	4750	4750
<i>precip</i>	8.25	8.25	6.65	6.65	6.65	6.65	6.65	6.65
<i>min_temp</i>	33	33	36	36	36	36	36	36
<i>max_temp</i>	65	65	67	67	67	67	67	67
<i>wet_days</i>	45	45	41	41	41	41	41	41
<i>freeze_thaw</i>	176	176	154	154	154	154	154	154
<i>rut_depth</i>	0.09	0.08	0.08	0.09	0.01	0.01	0.01	0.01
<i>lane\leq2</i>	1	1	1	1	1	1	1	1
<i>lane\geq3</i>	0	0	0	0	0	0	0	0
<i>nhs</i>	0	0	0	0	0	0	0	0
<i>stp</i>	1	1	1	1	1	1	1	1
<i>f_class=2</i>	0	0	0	0	0	0	0	0
<i>f_class=3</i>	0	0	0	0	0	0	0	0
<i>f_class=4</i>	0	0	0	0	0	0	0	0
<i>f_class=5</i>	1	1	1	1	1	1	1	1
<i>f_class=6</i>	0	0	0	0	0	0	0	0
<i>f_class=7</i>	0	0	0	0	0	0	0	0
<i>Category=2</i>	0	0	0	0	0	0	0	0
<i>Category=3</i>	1	0	0	0	0	0	0	0
<i>Category=4</i>	0	1	1	1	0	1	1	1
<i>Category=5</i>	0	0	0	0	0	0	0	0

846 **Table 2.** Estimation Parameters Used in the Experiments

Parameter	Value	Remarks
θ_0	10	Initial temperature
θ_{min}	10e-17	Final minimum temperature
B	30	Boltzmann constant
λ	0.97	Cooling rate
N_{max}	5	Number of neighborhood solutions generated at each temperature level
n	800	Minimum number of observations required in a cluster
N_{ps}	100	Number of pavement samples, which memberships were changed to generate a neighborhood cluster
VIF_{max}	10	Limiting VIF
α	5%	Level of Significance

847

848 **Table 3.** Estimated Model Parameters using the Proposed CLR Approach

Parameters	Cluster #1			Cluster #2			Cluster #3		
	β_{j1}	VIF	p-value	β_{j2}	VIF	p-value	β_{j3}	VIF	p-value
<i>intercept</i>	4.392	-	< 0.0001	4.552	-	< 0.0001	4.674	-	< 0.0001
<i>age</i>	-0.039	1.0	< 0.0001	-0.022	1.0	< 0.0001	-0.028	1.0	< 0.0001
<i>adt</i> [†]	-0.013	1.2	< 0.0001	-0.012	1.8	< 0.0001	-0.008	2.2	< 0.0001
<i>rut_depth</i>	-1.293	1.1	< 0.0001	-2.814	1.1	< 0.0001	-3.338	1.1	< 0.0001
<i>lane</i> ≤2	-	-	-	-0.191	4.4	< 0.0001	-0.358	4.4	< 0.0001
<i>lane</i> ≥3	-	-	-	-0.202	1.8	< 0.0001	-0.289	2.5	< 0.0001
<i>f_class</i> =2	-0.185	1.0	0.002	-	-	-	-	-	-
<i>f_class</i> =3	-0.110	1.6	< 0.0001	-	-	-	-	-	-
<i>f_class</i> =4	-0.259	1.5	< 0.0001	-	-	-	-	-	-
<i>f_class</i> =5	-1.052	1.4	< 0.0001	-	-	-	-	-	-
<i>f_class</i> =6	-1.181	1.1	< 0.0001	-	-	-	-	-	-
<i>f_class</i> =7	-0.284	1.0	0.006	-	-	-	-	-	-
<i>category</i> =2	-	-	-	-0.202	2.6	< 0.0001	-0.325	2.8	< 0.0001
<i>category</i> =3	-	-	-	-0.323	4.2	< 0.0001	-0.465	4.4	< 0.0001
<i>category</i> =4	-	-	-	-0.664	2.6	< 0.0001	-0.684	2.9	< 0.0001
<i>category</i> =5	-	-	-	-1.149	2.8	< 0.0001	-0.808	2.8	< 0.0001
<i>No. of Obs.</i>	2,376			2,483			2,442		
<i>BIC</i>	658			1,069			1,470		

Parameters	Cluster #4			Cluster #5			Cluster #6		
	β_{j4}	VIF	p-value	β_{j5}	VIF	p-value	β_{j6}	VIF	p-value
<i>intercept</i>	4.605	-	< 0.0001	4.557	-	< 0.0001	4.401	-	< 0.0001
<i>age</i>	-0.033	1.0	< 0.0001	-0.028	1.0	< 0.0001	-0.037	1.0	< 0.0001
<i>adt</i> [†]	-0.006	1.8	< 0.0001	-0.005	2.2	< 0.0001	-0.013	1.4	< 0.0001
<i>rut_depth</i>	-3.706	1.1	< 0.0001	-3.289	1.1	< 0.0001	-2.291	1.0	< 0.0001
<i>lane</i> ≤2	-0.213	4.8	< 0.0001	-0.260	4.9	< 0.0001	-	-	-
<i>lane</i> ≥3	-0.405	1.9	< 0.0001	-0.294	2.4	< 0.0001	-	-	-
<i>f_class</i> =2	-	-	-	-	-	-	0.468	1.2	< 0.0001
<i>f_class</i> =3	-	-	-	-	-	-	-0.086	1.5	< 0.0001
<i>f_class</i> =4	-	-	-	-	-	-	-0.258	1.4	< 0.0001
<i>f_class</i> =5	-	-	-	-	-	-	-0.864	1.3	< 0.0001
<i>f_class</i> =6	-	-	-	-	-	-	-1.288	1.1	< 0.0001
<i>f_class</i> =7	-	-	-	-	-	-	-0.634	1.0	< 0.0001
<i>category</i> =2	-0.263	3.0	< 0.0001	-0.194	2.7	< 0.0001	-	-	-
<i>category</i> =3	-0.325	4.0	< 0.0001	-0.287	4.2	< 0.0001	-	-	-
<i>category</i> =4	-0.650	3.2	< 0.0001	-0.639	3.1	< 0.0001	-	-	-
<i>category</i> =5	-0.808	3.4	< 0.0001	-1.130	2.9	< 0.0001	-	-	-
<i>No. of Obs.</i>	2,414			2,340			2,583		
<i>BIC</i>	1,009			1,273			870		

Note: † = variable value in thousands, and - = Not applicable

849

850

851 **Table 4.** Binary Matrix Showing Significance of the Explanatory Variables in the Estimated 6-

852 Cluster Models

Explanatory Variables	Cluster					
	$k = 1$	$k = 2$	$k = 3$	$k = 4$	$k = 5$	$k = 6$
<i>intercept</i>	1	1	1	1	1	1
<i>age</i>	1	1	1	1	1	1
<i>adt</i>	1	1	1	1	1	1
<i>elevation</i>	0	0	0	0	0	0
<i>precip</i>	0	0	0	0	0	0
<i>min_temp</i>	0	0	0	0	0	0
<i>max_temp</i>	0	0	0	0	0	0
<i>wet_days</i>	0	0	0	0	0	0
<i>rut_depth</i>	1	1	1	1	1	1
<i>lane</i> ≤2	0	1	1	1	1	0
<i>lane</i> ≥3	0	1	1	1	1	0
<i>nhs</i>	0	0	0	0	0	0
<i>stp</i>	0	0	0	0	0	0
<i>f_class</i> =2	1	0	0	0	0	1
<i>f_class</i> =3	1	0	0	0	0	1
<i>f_class</i> =4	1	0	0	0	0	1
<i>f_class</i> =5	1	0	0	0	0	1
<i>f_class</i> =6	1	0	0	0	0	1
<i>f_class</i> =7	1	0	0	0	0	1
<i>Category</i> =2	0	1	1	1	1	0
<i>Category</i> =3	0	1	1	1	1	0
<i>Category</i> =4	0	1	1	1	1	0
<i>Category</i> =5	0	1	1	1	1	0

853

854 **Table 5.** Metrics Calculated to Investigate the Presence of Overfitting in the Models

Metric	Value	Remarks
TSS	2,419	-
BCSS	4	0.17% of TSS
WCSS	2,415	-
SSR	1,130	47% of WCSS
SSE	1,284	53% of TSS

855

856 **Table 6.** RMSE, NRMSE, and MAE for Each Cluster

Metric	Cluster						Overall
	1	2	3	4	5	6	
RMSE	0.47	0.46	0.49	0.47	0.48	0.49	0.47
NRMSE	0.18	0.18	0.18	0.17	0.18	0.19	0.17
MAE	0.37	0.37	0.37	0.35	0.36	0.38	0.36